

Latex Satin 20 Basis1



Technical data

| | |
|-----------------|---|
| Specific use(s) | Protective coating |
| Density | 1,39 g/cm ³ |
| Wet-scrub | Class 1, complies with abrasion resistance in accordance with DIN 53778 |
| Contrast ratio | Class 2 (in accordance with DIN EN 13300) |
| Consumption | 150 ml/m ² |
| Gloss level | Silky gloss (in accordance with DIN EN 53778) |

Components

| | |
|--|---|
| Product Code/GISCODE | M-DF01 |
| Declaration of ingredients preservatives | Emulsion paint, emission-free and solvent-free contained |
| VOC content in accordance with Directive 2004/42/EC | < 0.1 % < 1 g/l |
| VOC content LEED [less water] | < 1 g/l |
| Solvent and plasticiser-free in accordance with VdL- RL 01 | yes |
| Water-dilutable in accordance with 2004/42/EC (Decopaint) | yes |
| Lead, cadmium, chromium VI * (* not contained in the formulation) | not contained |

Environmental labels

| | |
|--|------------|
| Complies with the VOC requirements in accordance with | RAL-UZ 102 |
|--|------------|

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

| No. | Application site | Product type | QS 1 | QS 2 | QS 3 | QS 4 |
|-----|--|---|------|------|------|------|
| 2 | Liquid coatings on primarily mineral undercoats, such as concrete, masonry, mortar, filler, plaster, wallpaper, fleece or plasterboard. Floor space and thoroughfares such as underground car parks, access roads, etc are not taken into account. | Decorative paints, decorative fillers, dust-binding coatings, floor coverings without special resistance requirements, concrete protection coatings | yes | yes | yes | yes |
| 27 | Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion. | Primer and top coating (e.g. paints, varnishes) | yes | yes | yes | yes |

Suitability for use in accordance with
LEED

Category (IEQ4.2 - 2009)

flat topcoat

VOC limit

50 g/l

Limit fulfilled

yes

Category (IEQ4.2 - 2009)

flat topcoat with colourant added at the point of sale

VOC limit

100 g/l

Limit fulfilled

yes

Recycling share

not contained

Production site

DAW SE

Roßdörfer Straße 50

DE-64372 Ober-Ramstadt