

ThermoSan NQG



Technical data

Specific use(s)	Water-borne coatings
Density	1,48 g/cm ³
Consumption	150 - 200 ml/m ²
Gloss level	Matt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE	M-SF01F; BSW50
Declaration of ingredients	Silicone resin paint, aqueous , with film protection
Preservation agents	contained
VOC content in accordance with Directive 2004/42/EC	< 3 %
VOC content LEED [less water]	< 40 g/l
Water-dilutable in accordance with 2004/42/EC (Decopaint)	< 80 g/l
Film protection	yes
Lead, cadmium, chromium VI *	contained (agent corresponds to 528/2012/EG)
(* not contained in the formulation)	not contained

Environmental labels

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
5	Coating materials for exterior mineral surfaces such as concrete, masonry, mineral mortar and filler, plaster, ETICS, wallpaper (façade wallpaper), plasterboard, etc.	Currently, just decorative paints and dispersion insulation adhesives are taken into account	VOC	Ja	Ja	Ja	Ja
31	Products with film preservation and good treated with biocides	Exterior plasters, façade coatings, floor coverings made of wool/natural fibres, wood glazes with film preservation	Biocides (product type 7 and 9 in accordance with 528/2012/EC: Preservatives for construction materials) e.g. algicides, fungicides, moth repellents	Ja	Ja	Ja	

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	not possible
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	flat topcoat with colourant added at the point of sale
VOC limit	100 g/l
Limit fulfilled	yes
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing Constructions (NaWoh) v3.1	suitable
--	----------