

Latex Samt 10



Technical data

Specific use(s)	Water-borne coatings
Density	1,35 g/cm ³
Wet-scrub	Class 1, complies with abrasion resistance in accordance with DIN 53778
Contrast ratio	Class 2 (in accordance with DIN EN 13300)
Consumption	140 - 160 ml/m ²
Gloss level	Silky matt (in accordance with DIN EN 53778)

Components

Product Code/GISCODE	M-DF01; BSW20
Declaration of ingredients	Emulsion paint, emission-free and solvent-free
Preservation agents	contained
VOC content in accordance with	< 0.1 %
Directive 2004/42/EC	< 1 g/l
VOC content LEED [less water]	< 1 g/l
Solvent and plasticiser-free in	yes
accordance with VdL- RL 01	
Water-dilutable in accordance with	yes
2004/42/EC (Decopaint)	
Lead, cadmium, chromium VI *	not contained
(* not contained in the formulation)	

Environmental labels

Complies with the VOC requirements in accordance with	RAL-UZ 102 (Blue Angel – Interior Wall Paints)
---	--

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
2	Coatings on predominantly mineral interior surfaces as well as on wallpaper, non-woven materials, plasterboard, etc. Floor areas with special resistance requirements (such as OS (surface protection) systems) and traffic routes such as underground garages and access roads are not taken into account	This refers to decorative paints, primers, decorative fillers (incl. Q-filler) and deep primer, floor coatings with no special resistance requirements, concrete glazes	VOC / SVOC	Ja	Ja	Ja	Ja

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	fulfilled
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	fulfilled
Product category	non flat topcoat
VOC limit	100 g/l
Limit fulfilled	yes
Product category	non-flat topcoat with colourant added at the point of sale
VOC limit	150 g/l
Limit fulfilled	yes
AgBB approval	passed
Formaldehyde limit <10µg/m ³ (28d)	fulfilled
Recycling share	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing Constructions (NaWoh) v3.1	suitable
--	----------