

# Capacryl PU-Gloss Basis R

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.08.2019	21.08.2019	Date of first issue: 20.08.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product id</b> Trade nar		:	Capad	cryl PU-Gloss Basis R
1.2 Relevant i	dentified uses of th	ne s	ubstar	ice or mixture and uses advised against
Use of the stance/Mi		:	Water	-borne coatings
Recomme on use	ended restrictions	:	within	adequate application - none
1.3 Details of	the supplier of the	saf	ety dat	a sheet
Company		:	Roßd	ol Farben Lacke GmbH örfer Straße 50 2 Ober-Ramstadt
Telephone	е		+4961	
Telefax	drace Deenensi			547170222
E-mail ad ble/issuin	dress Responsi- g person	:	msas	@dr-rmi.com
1.4 Emergenc	y telephone numb	er		
Emergeno ber 1	y telephone num-	:	+4961	3284463 GBK GmbH
<b>SECTION 2:</b>	Hazards identific	atio	on	
2.1 Classifica	tion of the substan	се	or mixt	ure
	ation (REGULATIO			
	itisation, Category 1	•	-0,110	H317: May cause an allergic skin reaction.
2.2 Label elen	nents			
Labelling	(REGULATION (E	C) N	lo 1272	2/2008)
Hazard pi	ctograms	:		
Signal wo	rd	:	Warnir	g
Hazard st	atements	:	H317	May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006

## **Capacryl PU-Gloss Basis R**

Version 1.0	Revision Date: 20.08.2019	Print Date 21.08.2019	Date of last issue: - Date of first issue: 20.08.2019
Preca	utionary statements	label at hand.	dical advice is needed, have product container or out of reach of children.
		P280 Wear	ot get in eyes, on skin, or on clothing. protective gloves/ eye protection.
		Response: P302 + P352 water.	IF ON SKIN: Wash with plenty of soap and

Hazardous components which must be listed on the label:

2-methylisothiazol-3(2H)-one

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

Chemical nature	:	Polyurethane/polyacrylate-based lacquer, aqueous
-----------------	---	--

## Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 603-096-00-8 01-2119475104-44	Eye Irrit. 2; H319	>= 1 - < 10
ammonia	1336-21-6 215-647-6 007-001-01-2 01-2119488876-14	Skin Corr. 1B; H314 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,1 - < 0,25
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1;	>= 0,0025 - < 0,025

according to Regulation (EC) No. 1907/2006

# **Capacryl PU-Gloss Basis R**

rsion )	Revision Date: 20.08.2019	Print Date 21.08.2019	Date of last issue: - Date of first issue: 20.08.2019	
1,2-be	enzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00- 01-2120761	Skin Irrit. 2; H315 6 Eye Dam. 1; H318	0,0025 - < 0,025
methy no. 24	on mass of: 5-chloro-2- /I-4-isothiazolin-3-one [E 47-500-7] and 2-methyl-2 azol-3-one [EC no. 220-2 1)	H - 613-167-00-	M-Factor (Chronic aquatic toxicity): 1 Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic	0,0002 - < 0,0015
Subst	ances with a workplace	exposure limit :	aquatic toxicity): 10	
	um dioxide	13463-67-7 236-675-5 01-2119489		= 1 - < 10

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice	<ul> <li>First aider needs to protect himself.</li> <li>Move out of dangerous area.</li> <li>If you feel unwell, seek medical advice (show the label where possible).</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
If inhaled	: Move to fresh air.

according to Regulation (EC) No. 1907/2006

## **Capacryl PU-Gloss Basis R**

Version 1.0	Revision Date: 20.08.2019	Print Date 21.08.2019	Date of last issue: - Date of first issue: 20.08.2019
In cas	e of skin contact	of water.	act, immediately flush skin with soap and plenty olvents or thinners.
In cas	e of eye contact	Remove conta rinsing.	inse cautiously with water for several minutes. ct lenses, if present and easy to do. Continue persists: Get medical advice/ attention.
lf swal	llowed		OO NOT induce vomiting. vith water and drink afterwards plenty of water. advice.

#### **4.2 Most important symptoms and effects, both acute and delayed** None known.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Unsuitable extinguishing None known. : media 5.2 Special hazards arising from the substance or mixture Specific hazards during fire-: In case of fire hazardous decomposition products may be fighting produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). 5.3 Advice for firefighters Special protective equipment : Wear self-contained breathing apparatus for firefighting if necfor firefighters essary. Further information 2 The product itself does not burn. Standard procedure for chemical fires. Use water spray to cool unopened containers.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures		
Personal precautions	: Do not get in eyes, on skin, or on clothing. Material can create slippery conditions. Use protective shoes or boots with rough rubber sole.	

according to Regulation (EC) No. 1907/2006

# **Capacryl PU-Gloss Basis R**

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.08.2019	21.08.2019	Date of first issue: 20.08.2019

### 6.2 Environmental precautions

Environmental precautions	<ul> <li>Do not flush into surface water or sanitary sewer system.</li> <li>If the product contaminates rivers and lakes or drains inform respective authorities.</li> <li>Prevent further leakage or spillage if safe to do so.</li> </ul>			
O Mathe is an investorial for a sufficiency of an independence				

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handling		
Advice on safe handling	:	No special technical protective measures required. For personal protection see section 8. Use only with adequate ventilation.
Hygiene measures	:	Do not eat, drink or smoke when using this product. Wash hands before eating, drinking, or smoking.
7.2 Conditions for safe storage, in	nclu	uding any incompatibilities
Requirements for storage areas and containers	:	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container. To maintain product quality, do not store in heat or direct sunlight. Perishable if frozen.
Advice on common storage	:	Keep away from oxidizing agents and strongly acid or alkaline materials.
Storage class (TRGS 510)	:	12, Non Combustible Liquids
7.3 Specific end use(s)		
Specific use(s)	:	Please follow the technical information.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2-	112-34-5	STEL	15 ppm	2006/15/EC

according to Regulation (EC) No. 1907/2006

# **Capacryl PU-Gloss Basis R**

rsion )	Revision Da 20.08.2019			ate of last issue: - ate of first issue: 20.08.2019	
butox oxy)e	yeth- thanol			101,2 mg/m3	
Furthe	er information	Indicative			-
			TWA	10 ppm 67,5 mg/m3	2006/15/E0
			AGW (Vapour and aerosols)	10 ppm 67 mg/m3	DE TRGS 900
	-limit: excur- actor (catego-	1.5;(I)		· · · · · · · · · · · · · · · · · · ·	·
Furth	er information	for the health a limit value: and aerosols.	(MAK-commission). deviations in value a , When there is com	v of compounds at the work p , European Union (The EU h nd peak limit are possible), s pliance with the OEL and bio rming the unborn child	as establishe Sum of vapor
titaniu	um dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900
	-limit: excur- actor (catego-	2;(II)			
Furthe	er information	value is estab unspecific act Commission f	lished, since the AG ion on the respirator or dangerous substa t the work place dan	ance no specific occupation S does not yet have informa y organs in excess of the no ances, Senate commission for gerous for the health (MAK-	ition regarding rmal values., or the review o commission).
			AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900
	-limit: excur- actor (catego-	2;(II)			

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
3,6-Bis(4- chloro- phenyl)pyrrolo[3,4- c]pyrrole-1,4(2H,5H)- dione	Consumers	Skin contact	Long-term systemic effects	1,66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,90 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,66 mg/kg bw/day
2-methylpentane-2,4- diol	Consumers	Inhalation	Long-term local ef- fects	25,00 mg/m3
	Consumers	Inhalation	Long-term systemic effects	3,50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,00 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	49,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,00 mg/kg bw/day
2-(2- butoxyethoxy)ethanol	Consumers	Inhalation	Acute local effects	60,70 mg/m3
	Consumers	Ingestion	Long-term systemic	200,00 mg/kg

according to Regulation (EC) No. 1907/2006

# Capacryl PU-Gloss Basis R

/ersion I.0	Revision Date: 20.08.2019		Print DateDate of last issue: -21.08.2019Date of first issue: 20.08.2019			
1				effects	bw/day	
		Consumers	Ingestion	Long-term systemic effects	5,00 mg/kg bw/day	
		Consumers	Skin contact	Long-term systemic effects	2000,00 mg/kg bw/day	
		Consumers	Inhalation	Long-term local ef- fects	40,50 mg/m3	
		Consumers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day	
		Consumers	Inhalation	Long-term systemic effects	40,50 mg/m3	
titaniu	um dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day	

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
3,6-Bis(4- chlorophenyl)pyrrolo[3,4- c]pyrrole-1,4(2H,5H)-dione	Fresh water sediment	377 mg/kg dry weight (d.w.)
	Fresh water	10 mg/l
	Soil	1 mg/kg dry weight (d.w.)
	Intermittent use/release	1 mg/l
	Marine sediment	37,7 mg/kg dry weight (d.w.)
	Sewage treatment plant	1 mg/l
	Marine water	1 mg/l
2-methylpentane-2,4-diol	Soil	0,11 mg/kg dry weight (d.w.)
	Intermittent use/release	4,29 mg/l
	Secondary Poisoning	100 mg/kg food
	Fresh water sediment	1,79 mg/kg dry weight (d.w.)
	Marine water	0,0429 mg/l
	Sewage treatment plant	20 mg/l
	Marine sediment	0,179 mg/kg dry weight (d.w.)
	Fresh water	0,429 mg/l
2-(2-butoxyethoxy)ethanol	Fresh water	1,1 mg/l
	Fresh water sediment	4,4 mg/kg dry weight (d.w.)
	Intermittent use/release	11 mg/l
	Marine water	0,11 mg/l
	Marine sediment	0,44 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Soil	0,32 mg/kg dry weight (d.w.)
	Secondary Poisoning	56 mg/kg food
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l

according to Regulation (EC) No. 1907/2006

# Capacryl PU-Gloss Basis R

Version Revision Date: 1.0 20.08.2019				Date of last issue: - Date of first issue: 20.08.2			
			Fresh water	sediment	1000 mg/kg dry weight (d.w.)		
			Marine sedin	nent	100 mg/kg dry weight (d.w.)		
			Intermittent u	ise/release	0,193 mg/l		
-	sure controls						
	onal protective equip						
Eye p	protection	:	German trade	association rules - BGR 192 E	ye protection		
			Goggles				
Ma Gl	protection aterial love thickness rotective index	:	Nitrile rubber 0,2 mm Class 3				
Re	emarks	:		gloves tested to EN374. Befor nem with soap and water.	e removing		
Skin a	and body protection	:	Long sleeved	clothing			
				protection according to the am ne dangerous substance at the			
			Skin should be	e washed after contact.			
			Safety shoes				
				vash contaminated clothing be application: impervious clothing			
Resp	iratory protection	:	No personal re quired.	espiratory protective equipmen	t normally re-		
			German trade tion	association rules - BGR 190 E	reathing protec-		
				application: Do not breathe spration filter for paint spraying.	ay dust. Use		

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	No data available
Odour	:	No data available
Odour Threshold	:	Not relevant
рН	:	not determined

according to Regulation (EC) No. 1907/2006

# **Capacryl PU-Gloss Basis R**

Version 1.0	n Revision Date: 20.08.2019		nt Date 08.2019	Date of last issue: - Date of first issue: 20.08.2019
М	elting point/freezing point	:	not determined	
В	oiling point/boiling range	:	not determined	
FI	ash point	:	not determined	
E١	vaporation rate	:	Not applicable	
	pper explosion limit / Upper ammability limit	:	not determined	
	ower explosion limit / Lower ammability limit	:	not determined	
Va	apour pressure	:	not determined	
R	elative vapour density	:	not determined	
R	elative density	:	not determined	
D	ensity	:	1,0800 g/cm3	
So	olubility(ies) Water solubility	:	completely miscil	ble
	artition coefficient: n- ctanol/water	:	not determined	
A	uto-ignition temperature	:	not determined	
D	ecomposition temperature	:	Not applicable	
Vi	iscosity Viscosity, dynamic	:	No data available	9
E	xplosive properties	:	Not applicable	
0	xidizing properties	:	Not applicable	
9.2 Otl	her information			
	ammability (liquids)	:	The product is no	ot flammable.

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.

## 10.2 Chemical stability

No decomposition if stored and applied as directed.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

# **Capacryl PU-Gloss Basis R**

Version 1.0	Revision Date: 20.08.2019		int Date .08.2019	Date of last issue: - Date of first issue: 20.08.2019
10.4 Cond	itions to avoid			
Condi	tions to avoid	:	Protect from fro	st, heat and sunlight.
10.5 Incon	npatible materials			
	als to avoid	:		th oxidizing agents. th acids and bases.
	dous decomposition	-		
SECTION	11: Toxicological i	nfor	mation	
11.1 Inforr	nation on toxicologic	al ef	fects	
	toxicity			
Produ	ict:			
Acute	oral toxicity	:	Remarks: Basec are not met.	on available data, the classification criteria
Acute	inhalation toxicity	:	Remarks: Basec are not met.	on available data, the classification criteria
Acute	dermal toxicity	:	Remarks: Basec are not met.	I on available data, the classification criteria
Comp	oonents:			
2-(2-b	utoxyethoxy)ethanol:	:		
Acute	oral toxicity	:	LD50 (Mouse): 2	2.410 mg/kg
			LD50 (Rat): 3.30	)5 mg/kg
Acute	dermal toxicity	:	LD50 (Rabbit): 2	2.764 mg/kg
2-met	hylisothiazol-3(2H)-oi	ne:		
	oral toxicity	:	LD50 (Rat): 120	mg/kg
Acute	inhalation toxicity	:	LC50 (Rat): 0,14 Exposure time: 4 Test atmosphere Remarks: see us	4 h
1,2-be	enzisothiazol-3(2H)-or	ne:		
Acute	oral toxicity	:	LD50 (Rat): 532	mg/kg
Acute	inhalation toxicity	:	LC50 (Rat): 0,4 Exposure time: 4 Test atmosphere	4 h
Acute	dermal toxicity	:	LD50 (Rat): > 2.	000 mg/kg

according to Regulation (EC) No. 1907/2006

# Capacryl PU-Gloss Basis R

Version 1.0	Revision Date: 20.08.2019		int Date .08.2019	Date of last issue: - Date of first issue: 20.08.2019
	tion mass of: 5-chloro-2-n iazol-3-one [EC no. 220-2			one [EC no. 247-500-7] and 2-methyl-2H -
Acut	e oral toxicity	:	LD50 (Rat): 66 m Method: OECD T	
Acut	e inhalation toxicity	:	LC50 (Rat): 0,17 Exposure time: 4 Test atmosphere: Method: OECD T	h
Acut	e dermal toxicity	:	LD50 (Rat): > 141 Method: OECD T	l mg/kg est Guideline 402
Skin	corrosion/irritation			
Prod				
Rem	arks	:		classification criteria of the European Union, considered as being a skin irritant.
Serie	ous eye damage/eye irri	itati	on	
Proc	luct:			
Rem	arks	:		classification criteria of the European Union, considered as being an eye irritant.
Resp	piratory or skin sensitis	atic	n	
Prod	luct:			
Rem	arks	:	Causes sensitisat	tion.
SECTIO	N 12: Ecological infor	ma	tion	
12.1 Toxi	city			
Proc	luct:			
Toxic	city to fish	:	Remarks: No data	a available
	city to daphnia and other ttic invertebrates	:	Remarks: No data	a available
<u>Com</u>	ponents:			

#### **2-methylisothiazol-3(2H)-one:** M-Factor (Acute aquatic tox- : 10)

icity)	•	10
		10
M-Factor (Chronic aquatic toxicity)	:	1

1

according to Regulation (EC) No. 1907/2006

# Capacryl PU-Gloss Basis R

Version 1.0	Revision Date: 20.08.2019	Print 21.08	Date 3.2019	Date of last issue: - Date of first issue: 20.08.2019		
1,2-	benzisothiazol-3(2H)-o	ne:				
M-F icity	actor (Acute aquatic tox- )	: 1				
M-F toxi	actor (Chronic aquatic city)	: 1				
	ction mass of: 5-chloro-2- hiazol-3-one [EC no. 220			one [EC no. 247-500-7] and 2-methyl-2H -		
M-F icity	actor (Acute aquatic tox-	: 1	00			
M-F toxi	actor (Chronic aquatic city)	: 1	0			
	sistence and degradab data available	ility				
12.3 Bio	accumulative potential					
<u>Cor</u>	mponents:					
	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1):					
	tition coefficient: n- anol/water			est Guideline 117		
	<b>bility in soil</b> data available					
12.5 Res	sults of PBT and vPvB a	assessi	nent			
Pro	duct:					
	essment	to Ve	be either persis	ixture contains no components considered tent, bioaccumulative and toxic (PBT), or d very bioaccumulative (vPvB) at levels of		
12.6 Oth	er adverse effects					
	<b>duct:</b> litional ecological infor- ion			hazard cannot be excluded in the event of ndling or disposal.		
	ON 13: Disposal consiste treatment methods	iderati	ons			
Pro	duct	: .				

Waste should not be disposed of via wastewater.

according to Regulation (EC) No. 1907/2006

## **Capacryl PU-Gloss Basis R**

Version 1.0	Revision Date: 20.08.2019	Print Date 21.08.2019	Date of last issue: - Date of first issue: 20.08.2019	
Contaminated packaging		: Only completely emptied containers should be given for recy- cling.		
Waste Code		: used product 080112, waste in 08 01 11*	080112, waste paint and varnish other than those mentioned	

## **SECTION 14: Transport information**

## 14.1 UN number

Not regulated as a dangerous good

## 14.2 UN proper shipping name

Not regulated as a dangerous good

## 14.3 Transport hazard class(es)

Not regulated as a dangerous good

## 14.4 Packing group

Not regulated as a dangerous good

## 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Remarks

: Not classified as dangerous in the meaning of transport regulations. see sections 6-8

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
: None
: Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
methanol (Number on list 69) formaldehyde (Number on list 72, 28)

according to Regulation (EC) No. 1907/2006

# **Capacryl PU-Gloss Basis R**

Version 1.0	Revision Date: 20.08.2019		int Date .08.2019	Date of last issue: - Date of first issue: 20.08.2019
	so III: Directive 2012/18 r-accident hazards invol			arliament and of the Council on the control of nces.
	er contaminating class many)	:	0,	ater endangering ording to AwSV, Annex 1 (5.2)
	uct code for laquers and s / Giscode	I :	M-LW01 Water-b	ased varnishes
		:	BSW30 Coating r	naterials, water-based, containing solvents
Volat	ile organic compounds	:	Directive 2004/42 < 4 % < 50 g/l	//EC

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## **SECTION 16: Other information**

#### Full text of H-Statements

Skin Sens.

2006/15/EC

H301 H302 H310 H311 H314 H315 H317 H318 H319 H330 H400 H410		Toxic if swallowed. Harmful if swallowed. Fatal in contact with skin. Toxic in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
H411 Full text of other abbreviation	ns	Toxic to aquatic life with long lasting effects.
Acute Tox. Aquatic Acute Aquatic Chronic Eye Dam. Eye Irrit. Skin Corr. Skin Irrit.		Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Skin corrosion Skin irritation

Europe. Indicative occupational exposure limit values

: Skin sensitisation

:

according to Regulation (EC) No. 1907/2006

## **Capacryl PU-Gloss Basis R**

Version 1.0	Revision Date: 20.08.2019	Print Date 21.08.2019	Date of last issue: - Date of first issue: 20.08.2019
2006/ 2006/	RGS 900 15/EC / TWA 15/EC / STEL RGS 900 / AGW	: Germany. TRO : Limit Value - e : Short term exp : Time Weighted	oosure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw -Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS -Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Coil do the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; ICS0 - Half maximal inhibitory concentration; IBCO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Ch

#### Further information

Classification of the mixtur	e:	Classification procedure:
Skin Sens. 1	H317	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## **REACH Information**

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

DE / EN