according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur Wetterschutzfarbe NQG Basis 3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Water-borne coatings

stance/Mixture

Recommended restrictions

on use

: within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

P101 If medical advice is needed, have product container or **Precautionary Statements**

label at hand.

P102 Keep out of reach of children.

Additional Labeling

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, octhilinone (ISO), 4,5-dichloro-2-octyl-

2H-isothiazol-3-one, 2-methyl-1,2-benzothiazol-3(2H)-one. May produce an

allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,0025 - <
	220-120-9	Skin Irrit. 2; H315	0,025
	613-088-00-6	Eye Dam. 1; H318	
	01-2120761540-60	Skin Sens. 1; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 2;	
		H411	
		Acute Tox. 2; H330	
		M-Factor (Acute	
		aquatic toxicity): 1	
		M-Factor (Chronic	
		aquatic toxicity): 1	
		aquatio toxioity).	
		specific concentration	
		limit	
		Skin Sens. 1; H317	
		>= 0,05 %	

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

		1	
octhilinone (ISO)	26530-20-1 247-761-7 613-112-00-5 01-2120768921-45	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti-	
		Acute oral toxicity: 125 mg/kg Acute inhalation tox- icity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg	
4,5-dichloro-2-octyl-2H-isothiazol-3-one	64359-81-5 264-843-8 613-335-00-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 100	

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Vers 5.0	sion		SDS 6007	Number: 643	of last issue: 25.01.2022 of first issue: 18.01.2023	
					M-Factor (Chronic aquatic toxicity): 100	
					specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 %	
					Acute toxicity esti- mate	
					Acute oral toxicity: 567 mg/kg Acute inhalation tox- icity (dust/mist): 0,16 mg/l	
	2-methy one	yl-1,2-benzothiazol-3(2l	H)-	2527-66-4 613-336-00-3	Acute Tox. 3; H301 Acute Tox. 4; H312 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 EUH071	>= 0,0002 - < 0,0015
					M-Factor (Acute aquatic toxicity): 1	
					specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
					Acute toxicity esti- mate	
					Acute oral toxicity: 175 mg/kg Acute dermal toxicity: 1.100 mg/kg	

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

Substances with a workplace exposure limit :			
Talc (Mg3H2(SiO3)4)	14807-96-6		>= 1 - < 10
	238-877-9		
	01-2120140278-58		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Move to fresh air.

In case of skin contact : Take off all contaminated clothing immediately.

Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

fire.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Use water spray to cool unopened containers.

Standard procedure for chemical fires. The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

Advice on safe handling Use only with adequate ventilation.

For personal protection see section 8.

No special technical protective measures required.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Wash hands before eating, drinking, or smoking. Do not eat, Hygiene measures

drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Keep away from oxidizing agents and strongly acid or alkaline Advice on common storage

materials.

Storage class (TRGS 510) 12

7.3 Specific end use(s)

Specific use(s) This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS
(Mg3H2(SiO3)4)		fraction)		900
	Peak-limit cat	egory: 2;(II)		
	Further information: When there is compliance with the OEL and biologic tolerance values, there is no risk of harming the unborn child			nd biological
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)		900
	Peak-limit cat	it category: 2;(II)		
	Further inform	Further information: When there is compliance with the OEL and biological		
	tolerance values, there is no risk of harming the unborn child			-
		BM (Alveolar	0,5 mg/m3	DE TRGS
		dust fraction)		527
octhilinone (ISO)	26530-20-1	AGW (Inhalable	0,05 mg/m3	DE TRGS

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

L		fraction)		900
		Peak-limit category: 2;(I)		
ſ		Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo-	Potential health ef-	Value
		sure	fects	
[(butoxymethyleth- oxy)methylethoxy]pro pan-1-ol	Consumers	Ingestion	Long-term systemic effects	25,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	25,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	50,00 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
[(butoxymethyleth-	Intermittent use/release	5,64 mg/l
oxy)methylethoxy]propan-1-ol		
	Fresh water sediment	2,59 mg/kg dry weight (d.w.)
	Fresh water	0,564 mg/l
	Sewage treatment plant	100 mg/l
	Sea water	0,0564 mg/l
	Sea sediment	0,259 ng/kg dry weight (d.w.)
	Soil	0,188 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

Long sleeved clothing

according to Regulation (EC) No. 1907/2006

according to Regulation (EC) No. 1907/20



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

> Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

Odor : No data available

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8-9

Concentration: 100 %

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : completely miscible

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Density : 1,0800 g/cm3

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

octhilinone (ISO):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

Acute oral toxicity : Acute toxicity estimate: 567 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,16 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

2-methyl-1,2-benzothiazol-3(2H)-one:

Acute oral toxicity : Acute toxicity estimate: 175 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Skin corrosion/irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Not skin sensitising on the basis of the results of similar tested

mixtures, applying bridging principles in accordance with CLP Regulation Article 9(4). Result of studies: Sensitization OECD

429 (LLNA) (mouse) not sensitizing

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna Straus (Water flea)): > 10 mg/l

End point: Immobilization Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): 100

End point: Growth inhibition

Exposure time: 72 h

Test Type: Growth inhibition Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (green algae)): End

point: Growth inhibition Exposure time: 72 h

Test Type: Cell multiplication inhibition test

Method: OECD Test Guideline 201

GLP: no

Ecotoxicology Assessment

Chronic aquatic toxicity This product has no known ecotoxicological effects.

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

toxicity)

octhilinone (ISO):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

toxicity)

: 100

4,5-dichloro-2-octyl-2H-isothiazol-3-one:

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

toxicity)

: 100

2-methyl-1,2-benzothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 1

icity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

octhilinone (ISO):

Partition coefficient: n- : log Pow: 2,92

octanol/water Method: OECD Test Guideline 117

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product :

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recy-

cling.

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regu-

lations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

REACH - List of substances subject to authorisation : None

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

ving

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Not applicable

. : BSW50 Coating materials, water-based, containing solvents,

film-protected

Volatile organic compounds : Directive 2004/42/EC

< 1 % < 10 g/l

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur Wetterschutzfarbe NQG Basis 3

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.01.2022

 5.0
 18.01.2023
 6007643
 Date of first issue: 18.01.2023

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Stemegency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth response; EMS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Coil Aviation Organization; IECSC - Inventy of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Convention for Standardization; IECSC - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse) Effect Sandardization; NOELR - No O

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

according to Regulation (EC) No. 1907/2006

DE / EN



Capadur Wetterschutzfarbe NQG Basis 3

Version Revision Date: SDS Number: Date of last issue: 25.01.2022 5.0 18.01.2023 6007643 Date of first issue: 18.01.2023

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN