according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capacryl EffektLack sm. Silber RAL 9006

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Water-borne coatings

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH

Roßdörfer Straße 50 64372 Ober-Ramstadt

Telephone : +496154710 Telefax : +4961547170222

E-mail address Responsi-

ble/issuing person

: msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

P101 If medical advice is needed, have product container or **Precautionary Statements**

label at hand.

P102 Keep out of reach of children.

Additional Labeling

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

EUH208

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2Hisothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
propan-2-ol	67-63-0	Flam. Liq. 2; H225	>= 1 - < 10
	200-661-7	Eye Irrit. 2; H319	
	603-117-00-0	STOT SE 3; H336	
	01-2119457558-25		
titanium dioxide; [in powder form	13463-67-7	Carc. 2; H351	>= 0,1 - < 1
containing 1 % or more of parti-	236-675-5		
cles with aerodynamic diameter ≤	022-006-00-2		
10 μm]	01-2119489379-17		
1,2-benzisothiazol-3(2H)-one	2634-33-5	Acute Tox. 4; H302	>= 0,025 - <
	220-120-9	Skin Irrit. 2; H315	0,05
	613-088-00-6	Eye Dam. 1; H318	
	01-2120761540-60	Skin Sens. 1; H317	
		Aquatic Acute 1;	
		H400	
		Aquatic Chronic 2;	
		H411	
		Acute Tox. 2; H330	
		M-Factor (Acute	
		aquatic toxicity): 1	

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 20.12.2022 6011149 Date of first issue: 10.12.2019

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 >= 0,05 % Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0002 - < 0,0015
aluminium powder (stabilised)	7429-90-5	Flam. Sol. 1; H228	>= 1 - < 10
	231-072-3 013-002-00-1 01-2119529243-45		
(2-methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		>= 1 - < 10

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled Move to fresh air.

In case of skin contact Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

If eye irritation persists: Get medical advice/ attention. In case of eye contact

> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Do not use a solid water stream as it may scatter and spread

fire.

Unsuitable extinguishing

media

: None known.

according to Regulation (EC) No. 1907/2006

DE / EN



Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Further information : Use water spray to cool unopened containers.

Standard procedure for chemical fires. The product itself does not burn.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use protective shoes or boots with rough rubber sole.

Material can create slippery conditions. Do not get in eyes, on skin, or on clothing.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only with adequate ventilation.

For personal protection see section 8.

No special technical protective measures required.

In addition, the current technical information for this product

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

and its application on www.caparol.com must be observed.

Wash hands before eating, drinking, or smoking. Do not eat, Hygiene measures

> drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating

areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Perishable if frozen. To maintain product quality, do not store in heat or direct sunlight. Store at room temperature in the original container. Containers which are opened must be care-

fully resealed and kept upright to prevent leakage.

Keep away from oxidizing agents and strongly acid or alkaline Advice on common storage

materials.

Storage class (TRGS 510) 12

7.3 Specific end use(s)

Specific use(s) This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
aluminium powder	7429-90-5	AGW (Inhalable	10 mg/m3	DE TRGS	
(stabilised)		fraction)		900	
	Peak-limit cat	egory: 2;(II)			
	Further inform	nation: When there is	compliance with the OEL ar	nd biological	
	tolerance valu	ies, there is no risk o	of harming the unborn child		
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)		900	
	Peak-limit category: 2;(II)				
	Further information: When there is compliance with the OEL and biological				
	tolerance values, there is no risk of harming the unborn child				
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)		527	
(2-	34590-94-8	TWA	50 ppm	2000/39/EC	
methoxymeth-			308 mg/m3		
ylethoxy)propanol					
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		AGW (Vapour	50 ppm	DE TRGS	

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 20.12.2022 6011149 Date of first issue: 10.12.2019

		and aerosols)	310 mg/m3	900	
	Peak-limit category: 1;(I)				
propan-2-ol	67-63-0	AGW	200 ppm	DE TRGS	
			500 mg/m3	900	
	Peak-limit cat	egory: 2;(II)			
	Further inform	nation: When there is	compliance with the OEL ar	nd biological	
	tolerance valu	ies, there is no risk o	of harming the unborn child		
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900	
	Peak-limit category: 2;(II)				
	Further information: When there is compliance with the OEL and biological				
	tolerance valu		of harming the unborn child	T	
		AGW (Alveolate	1,25 mg/m3	DE TRGS	
		fraction)	(Titanium dioxide)	900	
	Peak-limit cat	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological				
	tolerance values, there is no risk of harming the unborn child				
		BM (Alveolar	0,5 mg/m3	DE TRGS	
		dust fraction)		527	

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
aluminium powder (stabilised)	7429-90-5	Aluminum: 50 µg/g creatinine (Urine)	In case of long- term exposure: after more than one shift	TRGS 903
propan-2-ol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo-	Potential health effects	Value
aluminium powder (stabilised)	Consumers	Ingestion	Long-term systemic effects	7,90 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	3,95 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,72 mg/m3
	Workers	Inhalation	Long-term local ef-	3,72 mg/m3

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 20.12.2022 6011149 Date of first issue: 10.12.2019

			fects	
(2- methoxymethyleth- oxy)propanol	Consumers	Ingestion	Long-term systemic effects	0,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	475,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	202,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	36,00 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	121,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	37,20 mg/m3
	Workers	Inhalation	Long-term systemic effects	308,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	404,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	283,00 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	950,00 mg/kg bw/day
propan-2-ol	Consumers	Skin contact	Long-term systemic effects	319,00 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	89,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	26,00 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	500,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	888,00 mg/kg bw/day
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 µm]	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local ef- fects	10,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

	, , , , , , , , , , , , , , , , , , , ,	
Substance name	Environmental Compartment	Value
aluminium powder (stabilised)	Sewage treatment plant	20 mg/l
	Fresh water	74,9 µg/l
(2-	Soil	2,2 mg/kg dry
methoxymethylethoxy)propanol		weight (d.w.)
	Intermittent use/release	192 mg/l
	Fresh water	19,2 mg/l

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 20.12.2022 6011149 Date of first issue: 10.12.2019

	Sewage treatment plant	4168 mg/l
	Sea water	1,92 mg/l
	Intermittent use/release	190 mg/l
	Fresh water sediment	70,2 mg/kg dry weight (d.w.)
	Sea water	1,9 mg/l
	Soil	2,74 mg/kg dry weight (d.w.)
	Sea sediment	7,02 mg/kg dry weight (d.w.)
	Fresh water	19 mg/l
propan-2-ol	Sewage treatment plant	2251 mg/l
	Fresh water sediment	552 mg/kg dry weight (d.w.)
	Sea sediment	552 mg/kg dry weight (d.w.)
	Fresh water	140,9 mg/l
	Intermittent use/release	140,9 mg/l
	Soil	28 mg/kg dry weight (d.w.)
	Secondary Poisoning	160 mg/kg food
	Sea water	140,9 mg/l
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Sea water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sea sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber Glove thickness : 0,2 mm Protective index : Class 3

Remarks : Before removing gloves clean them with soap and water.

according to Regulation (EC) No. 1907/2006

DE / EN



Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

Wear suitable gloves tested to EN374.

DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

Odor : No data available

Melting point/freezing point : ca. 0 °C

Boiling point/boiling range : ca. 100 °C

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower :

flammability limit

not determined

Flash point : Not applicable

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 8-9

Concentration: 100 %

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

Viscosity

Viscosity, dynamic : No data available

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : ca. 23,4 hPa (20 °C)

Relative density : not determined

Density : 1,0500 g/cm3

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : The product is not flammable.

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 4.570 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 13.400 mg/kg

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 532 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Acute oral toxicity : LD50 (Rat): 66 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 141 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic : 1

toxicity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

M-Factor (Acute aquatic tox-100

icity)

M-Factor (Chronic aquatic 100

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

propan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 0,05

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

(3:1):

Partition coefficient: nlog Pow: <= 0,71

octanol/water Method: OECD Test Guideline 117

(2-methoxymethylethoxy)propanol:

Partition coefficient: n-: Pow: 1,01 (25 °C)

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006



DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste should not be disposed of via wastewater.

: Only completely emptied containers should be given for recy-Contaminated packaging

Waste Code used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN Not regulated as a dangerous good ADR Not regulated as a dangerous good RID Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.2 UN proper shipping name

ADN Not regulated as a dangerous good **ADR** Not regulated as a dangerous good RID Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

DE / EN



Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

IMDG : Not regulated as a dangerous goodIATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regu-

lations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: formaldehyde (Number on list 72,

dibutyltin dilaurate (Number on list 30)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above

according to Regulation (EC) No. 1907/2006

DE / EN



Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

> 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener-

ated.

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

ny)

WGK 1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

paints / Giscode

Product code for laquers and : M-LW01 Water-based varnishes

: BSW30 Coating materials, water-based, containing solvents

: Directive 2004/42/EC Volatile organic compounds

> < 5 % < 60 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H225 Highly flammable liquid and vapor.

H228 Flammable solid. Toxic if swallowed. H301 Harmful if swallowed. H302 H310 Fatal in contact with skin.

according to Regulation (EC) No. 1907/2006

CAPAROL

DE / EN

Capacryl EffektLack sm. Silber RAL 9006

Version 2.0	Revision Date: 20.12.2022		OS Number: 11149	Date of last issue: 10.12.2019 Date of first issue: 10.12.2019
H314 H315 H317 H318 H339 H336 H351 H400 H410 H411	74	: : : : : : : : : : : : : : : : : : : :	Causes skin irrita May cause an alle Causes serious e Causes serious e Fatal if inhaled. May cause drows Suspected of cau Very toxic to aqua Very toxic to aquatic li	ergic skin reaction. ye damage. ye irritation. iness or dizziness. sing cancer if inhaled. atic life. atic life with long lasting effects. fe with long lasting effects.
EUNU	<i>t</i> 1	•	Corrosive to the r	espiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable solids

Flam Sol : Flammable solids

Flam. Sol. : Flammable solids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization
STOT SE

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours
DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AlIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Covil Aviation Organization; IECSC - Inventory of Existing Chemicals Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observed (Adverse)

according to Regulation (EC) No. 1907/2006

DE / EN



Capacryl EffektLack sm. Silber RAL 9006

Version Revision Date: SDS Number: Date of last issue: 10.12.2019 2.0 20.12.2022 6011149 Date of first issue: 10.12.2019

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs. Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN